

Introducing the Sonic™-V Series portfolio of elegantly simple, technologically advanced and user-friendly **Wideband Multibeam Echosounder systems**.

Unique user benefits for every application:

► Compact VOX-IM

- Serial connectors for Motion, GNSS time messages and Sound Velocity Probe
- Wide range of voltage input - AC and DC

► VOX Control User Interface

- Fresh look, modern interface that is agile, intuitive and user-friendly
- Improved logic and layout of advanced settings
- Configurable hotkeys, language translations and help feature

► Ultra High Density (UHD)

- Up to 1024 true soundings per ping for improved data density across the swath

► Technical Modes that can be upgraded remotely, anytime

- 700kHz Ultra High Resolution (UHR) available for all systems
- 90/100kHz extended sounding depth for 2026-V
- TruePix® / Multispectral backscatter with compressed water column
- Switchable forward looking sonar (FLS)

► Depth Rating: 100m / 4000m / 6000m (6000m available on 2024-V)

► Standard 3-year warranty, with option to extend to 6-years

- Minimize your risk on investment
- Fast, quality repairs performed by the team that engineered the sonar
- Theoretical and hands-on personalized training delivered by our experts



Sonic 2020-V with optional mounting bracket



Compact VOX-IM



VOX Control User Interface



2022-V with optional mounting bracket

Easy to Integrate on any platform



*AUV



ROV



ASV/USV



Survey Vessel

Extra Light & Compact!





	Sonic™ 2020-V	Sonic™ 2022-V	Sonic™ 2024-V	Sonic™ 2026-V
Selectable Frequencies	200kHz - 450kHz. Optional 700kHz	170 - 450kHz. Optional 700kHz	170 - 450kHz. Optional 700kHz	170-450kHz. Optional 90/100kHz and 700kHz
Minimum frequency increase			1Hz	
Beamwidth, across track and along track	1° x 1° at 700kHz (optional) 1.8° x 1.8° at 450kHz 4° x 4° at 200kHz	0.6° x 0.6° at 700kHz (optional) 0.9° x 0.9° at 450kHz 2° x 2° at 200kHz	0.3° x 0.6° at 700kHz (optional) 0.45° x 0.9° at 450kHz 1° x 2° at 200kHz	0.3° x 0.3° at 700kHz (optional) 0.45° x 0.45° at 450kHz 1° x 1° at 200kHz 2° x 2° at 90/100kHz (optional)
Number of soundings		Up to 1024 soundings per ping		
Max speed (vessel)		11 knots (*)		
Near-field focusing		Yes		
Roll stabilized beams		Yes		
Pitch stabilized beams	Yes		No	Yes
ROBO Automated Operation		Yes Auto Power, pulse width, RangeTrac, GateTrac, SlopeTrac		
Saturation monitor		Yes		
Selectable Swath Sector (also referred as Max Coverage)	10° to 130°, up to 160° through engineering command User selectable in real-time	10° to 160° User selectable in real-time		
Sounding Patterns		Equiangular Equidistant single / double / quad modes Ultra High Density (UHD)		
Sounding Depth**	up to 200m	up to 500m		up to 800m+
Pulse Length		15µs - 1.115ms		15µs - 2ms 140µs – 2ms in LF mode
Ping rate		up to 60Hz		
Immersion Depth	100m Optional 4000m	100m Optional 4000m FLS projectors are rated at 3000m	Optional 4000m & 6000m FLS projectors are rated at 3000m	100m Optional 4000m FLS projectors are rated 4000m
Bottom Detect Resolution		3mm		

Electrical Interface

Mains	90-260V AC, 45-65Hz, or 10-55V DC			
Power consumption	20W avg	35W avg	50W avg	100W avg
Uplink/downlink	10/100/1000Base-T Ethernet			
Sync in, Sync out	TTL			
Deck cable length	15m, optional 25m and 50m			

Mechanical Specifications

Sonar Dimension (LWD)	140 x 161 x 133.5 mm			
Sonar Mass	4.4kg			
Receiver Dim (LWD)		276 x 109 x 190 mm	480 x 109 x 190 mm	
Receiver Mass		7.7kg	12.9kg	
Projector Dim (LWD)		273 x 108 x 86 mm	480 x 109 x 196 mm	
Projector Mass		3.3kg	13.4kg	
VOX-IM Interface Module (LWH) & Mass	212 x 160 x 70.5 mm; 2.9kg			

(*) The speed of the survey is primarily limited by the installation of the MBES.

(**) Depending on environmental conditions.

Specification Sheet 2025 version 2E subject to change without notice